




FDV SPEC SHEET

Gyre Up&Down 800lm 830 24° 10W BK

Art. no: 101520-24-2

Ledpro
by NORLUX



Gyre Up&Down 800lm 830 24° 10W BK



Art. no: 101520-24-2

LYS TEKNISK

Lumen ut (lm):	760
Lumen LED (tc=25):	800
Spredningsvinkel [°]:	24°
Fargetemperatur [K]:	3000
Fargegjengivelse [CRI/Ra]:	80
Fargekode:	830
Fargetoleranse [SDCM]:	3
Optikk:	Clear

MONTERING / TILKOBLING

Tilkobling:	QuickConnect
Montering:	Vegg

ELEKTRISK DATA

Dimmetype:	None
Systemeffekt [W]:	10
Spennning [V]:	230V 50Hz
Isolasjonsklasse:	1
Maks belastning pr kurs - B10:	95
Maks belastning pr kurs - B16:	152
Maks belastning pr kurs - C10:	90
Maks belastning pr kurs - C16:	152
Lekkasjestrøm [mA]:	0,75
Startstrøm I _{max} [A]:	6,2
Startstrøm tid [µs]:	65
Sokkel :	N/A
Strøm LED [mA]:	230



FDV SPEC SHEET

Gyre Up&Down 800lm 830 24° 10W BK

Art. no: 101520-24-2



PRODUKT

IP-grad:	IP65
Vandal klasse:	IK06
Driftstemperatur [°C]:	-20 - 40
Forventet Levetid :	L80B10: 50.000
Farge :	Black
Lengde [mm]:	105
Høyde [mm]:	170
Bredde [mm]:	60
Vekt [kg]:	0,6