




FDV SPEC SHEET

Cobra 360° Rotatable Surface

Art. no: 6827-D2W-38-2

Ledpro
by NORLUX



Cobra 360° Rotatable Surface



Art. no: 6827-D2W-38-2

LYS TEKNISK

Lumen ut (lm):	470
Lumen LED (tc=25):	550
Spredningsvinkel [°]:	38°
Fargetemperatur [K]:	3000-2000K D2W
Fargegjengivelse [CRI/Ra]:	90
Fargekode:	930-920
Fargetoleranse [SDCM]:	3
Optikk:	Clear

MONTERING / TILKOBLING

Tilkobling:	QuickConnect
Montering:	Tak, Utenpåliggende

ELEKTRISK DATA

Dimmetype:	Phase-Cut
Systemeffekt [W]:	8
Spennning [V]:	230V 50Hz
Isolasjonsklasse:	2
Belastning pr kurs - B10:	35
Belastning pr kurs - B16:	56
Belastning pr kurs - C10:	74
Belastning pr kurs - C16:	118
Startstrøm I _{max} [A]:	5
Startstrøm tid [µs]:	300
Sokkel :	N/A



FDV SPEC SHEET

Cobra 360° Rotatable Surface

Art. no: 6827-D2W-38-2



PRODUKT

Monteres rett i isolasjon:	Not applicable
IP-grad:	IP20
Driftstemperatur [°C]:	-
Forventet Levetid :	50 000
Farge :	Black
Lengde [mm]:	100
Høyde [mm]:	83
Bredde [mm]:	79
Vekt [kg]:	0,6