

FIL 2.5W 15000h BX

Pure white light – 360° light distribution

The unique feature of this series is the lamps' fully comprehensive 360-degree light distribution. The lamp also emits light in the direction of the base, which is particularly useful for ceiling luminaires, for example. An opal cover makes the light glareless. Models that are dimmable with LED dimmers can be recognised by the DIM symbol on the package. The lamps have a pleasant pure white tone (3000 K). Their eco-friendly cardboard packages are colour-coded. The colour indicates the corresponding incandescent bulb, making the choice simpler for the consumer. Technical specifications are also clearly presented.

Opal P45 bulb filament LED lamp 2.5W 3000K E27
250lm 15000h 45x78mm, full glass, cardboard
packing. Supply frequency ~50/60Hz.



FIL 2.5W 15000h BX			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4713498	A7GABS	0.02	Decor

FIL 2.5W 15000h BX
EC001959

Mounting

Degree of protection (IP)	Other
---------------------------	-------

Structure

Colour housing	White
Energy efficiency class	F
Colour	White

Dimming and control

With remote control	No
Dimmable	No
Remote operation possible	No

Photometric data

Colour temperature (min) (K)	3000
Luminous flux (min) (lm)	250
Colour rendering index CRI	80-89
Colour of light acc. EN 12464-1	Warm <3300 K
Colour temperature (max) (K)	3000
Luminous flux (max) (lm)	250
Colour consistency (McAdam ellipse)	SDCM6
Photobiological safety according to EN 62471	RG1

Lifetime and capacity

Measurements

Length (mm)	78
Diameter (mm)	45

Electrotechnical data

Voltage type	AC
Nominal voltage (min) (V)	220
Nominal current (min) (mA)	20
Nominal voltage (max) (V)	240
Nominal current (max) (mA)	19
Total harmonic distortion	135
Power factor	0.4
Energy Efficiency Index (EEI)	0.096