



FDV SPEC SHEET

Driver 700mA cc 30W 21-43V Phasecut AcTec 18i3 Male/EPN0034

Art. no: D70030NTF-03



Driver 700mA cc 30W 21-43V Phasecut AcTec 18i3 Male



Art. no: D70030NTF-03

MONTERING / TILKOBLING

Tilkobling: 18i3 Hurtigkobling

PRODUKT

IP-grad: IP20

Driftstemperatur [°C]: -20 - 50

Lengde [mm]: 142

Høyde [mm]: 24

Bredde [mm]: 50

Vekt [kg]: 0,2

ELEKTRISK DATA

Dimmetype: Faseavsnitt

Dimming Output Type: Amplitude Modulation

Dimming Phasecut Type: Leading / Trailing edge

Flimmerfri: Ja

Flicker metric (Pst LM) <: 1

Stroboscopic effect metric (SVM) <: 0,4

Spennings [V]: 230V 50Hz

Isolasjonsklasse: 2

Belastning pr kurs - B10: 35

Belastning pr kurs - B16: 56

Belastning pr kurs - C10: 74

Belastning pr kurs - C16: 118

Lekkasjestrøm [mA]: 7

Startstrøm I_{max} [A]: 5

Startstrøm tid [μs]: 300