



PRODUCT SHEET

Driver DALI 700mA max 36W 30-42V 18i5 DALI/EPN0034

Art. no: 0300-2-17



Driver DALI 700mA max 36W 30-42V 18i5 DALI/EPN003



SPECIFICATIONS

System Effekt [W]:	36W
Dimming:	DALI2
Standby power Psb (W) <:	0,5
Flicker metric (Pst LM) <:	0,4
Stroboscopic effect metric (SVM) <:	0,1
CC eller CV:	CC
CC [mA]:	700 - 850mA
CC (driver spenning ut) [V]:	30 - 42V
Maks Spenning ut [V]:	60
Strøm Toleranse [%]:	5%
Strøm Ripple [%]:	4%
Strømminnstilling:	DIP-switch
Forventet Levetid:	50000h
Spenning [V]:	230V 50HzV
Isolasjonsklasse:	2
Dimming Minimum Level :	1%
Dimming output type:	Amplitude Modulation
Maks belastning per kurs - B10:	28
Maks belastning per kurs - B16:	36
Maks belastning per kurs - C10:	37
Maks belastning per kurs - C16:	50
Lekkasjestrøm [mA]:	0,7mA
Startstrøm I _{max} [A]:	16,5A
Startstrøm tid [μs]:	177μs
Produsent:	Philips
Tilkobling Primær:	18i5 DALI hann
Tilkobling Sekundær:	EPN0034 hunn



PRODUCT SHEET

Driver DALI 700mA max 36W 30-42V 18i5 DALI/EPN0034

Art. no: 0300-2-17



Farge :

Hvit