



FDV SPEC SHEET

Nereus M/S 1850lm 830/840/857 60° 12W WH PIR Ø160-170mm

Art. no: 102620-S-60-3



Nereus M/S 1850lm 830/840/857 60° 12W WH PIR Ø16



Art. no: 102620-S-60-3

LYS TEKNISK

Lyskilde :	LED (innebygget)
Lumen ut (lm):	1660
Lumen LED (tc=25):	1850
Spredningsvinkel [°]:	60°
Fargetemperatur [K]:	3/4/5700
Forhåndsinnstilt Fargetemperatur	3000
Fargegjengivelse [CRI/Ra]:	80
Fargekode:	830/840/857

MONTERING / TILKOBLING

Tilkobling:	Hurtigkobling
Utsparring [mm]:	Ø160-170mm
Montering:	Innfelt, Tak

PRODUKT

Monteres rett i isolasjon:	Not applicable
IP-grad:	IP44
Driftstemperatur [°C]:	-20 - 40
Forventet Levetid :	L80B10: 100 000
Farge :	Hvit
RAL:	RAL9016

ELEKTRISK DATA

UGR (<=):	19
Dimmetype:	Sensor (PIR)
Systemeffekt [W]:	12
Spenning [V]:	230V 50Hz
Isolasjonsklasse:	2
Lekkasjestrøm [mA]:	0,16
Sokkel :	N/A