




FDV SPEC SHEET

Pavo P

Art. no: 8017646

Ledpro
by NORLUX



L, mm	W, mm	A, mm	B, mm	C, mm
280	95	135	87	77.5
360	105	196	104	123
410	115	239	157	149.5
500	140	317	191.5	124.5

Pavo P



A⁺

Art. no: 8017646

LYS TEKNISK

Lyskilde :	LED (innebygget)
Lumen ut (lm):	2090
Lumen LED (tc=25):	2090
Spredningsvinkel [°]:	118
Fargetemperatur [K]:	3000
Fargegjengivelse [CRI/Ra]:	80
Fargekode:	830
Fargetoleranse [SDCM]:	5
Optikk:	Opal
UGR (<=):	22

MONTERING / TILKOBLING

Tilkobling:	Terminal
Montering:	Tak, Utenpåliggende, Vegg

ELEKTRISK DATA

Dimmetype:	Ingen
Systemeffekt [W]:	22
Spennning [V]:	230V 50Hz
Isolasjonsklasse:	1
Sokkel :	N/A
Nøddlys [t]:	3 timer
Nøddlys testfunksjon:	Selvtest



FDV SPEC SHEET

Pavo P

Art. no: 8017646



PRODUKT

IP-grad:	IP44
Vandal klasse:	IK02
Driftstemperatur [°C]:	-15 - 35
Forventet Levetid :	L70B50: 40 000
Farge :	Hvit
RAL:	RAL9003
Lengde [mm]:	410
Høyde [mm]:	115
Bredde [mm]:	410
Vekt [kg]:	0,9