



## PRODUCT SHEET

Driver On/Off 900mA Panel max 44W 18i3 Male/ EPN0034

Art. no: 0300-2-03



# Driver On/Off 900mA Panel max 44W 18i3 Male/ EPN0



### SPECIFICATIONS

|                                     |              |
|-------------------------------------|--------------|
| System Effekt [W]:                  | 44W          |
| Dimming:                            | Ingen        |
| Standby power Psb (W) <:            | 0,5          |
| Flicker metric (Pst LM) <:          | 0,06         |
| Stroboscopic effect metric (SVM) <: | 0,07         |
| CC eller CV:                        | CC           |
| CC [mA]:                            | 900 - 1050mA |
| CC (driver spenning ut) [V]:        | 30 - 42V     |
| Maks Spenning ut [V]:               | 60           |
| Strøm Toleranse [%]:                | 8%           |
| Strøm Ripple [%]:                   | 1%           |
| Strømminnstilling:                  | DIP-switch   |
| Forventet Levetid:                  | 50000h       |
| Spenning [V]:                       | 230V 50HzV   |
| Isolasjonsklasse:                   | 2            |
| Maks belastning per kurs - B10:     | 32           |
| Maks belastning per kurs - B16:     | 40           |
| Maks belastning per kurs - C10:     | 42           |
| Maks belastning per kurs - C16:     | 56           |
| Lekkasjestrøm [mA]:                 | 0,7mA        |
| Startstrøm I <sub>max</sub> [A]:    | 19,5A        |
| Startstrøm tid [μs]:                | 258μs        |
| Produsent:                          | Philips      |
| Tilkobling Primær:                  | 18i3 hann    |
| Tilkobling Sekundær:                | EPN0034 hunn |