



PRODUCT SHEET

Driver DALI 900mA Panel max 40W CLO 18i5 DALI/EPN0034

Art. no: 0300-2-04



Driver DALI 900mA Panel max 40W CLO 18i5 DALI/EPN



SPECIFICATIONS

System Effekt [W]:	40W
Dimming:	DALI2
Standby power Psb (W) <:	0,5
Flicker metric (Pst LM) <:	0,4
Stroboscopic effect metric (SVM) <:	0,4
CC eller CV:	CC
CC [mA]:	900 - 1050mA
CC (driver spenning ut) [V]:	30 - 42V
Maks Spenning ut [V]:	60
Strøm Toleranse [%]:	5%
Strøm Ripple [%]:	4%
Strømminnstilling:	DIP-switch
Forventet Levetid:	50000h
Spenning [V]:	230V 50HzV
Isolasjonsklasse:	2
Dimming Minimum Level :	1%
Dimming output type:	Amplitude Modulation
Maks belastning per kurs - B10:	29
Maks belastning per kurs - B16:	36
Maks belastning per kurs - C10:	37
Maks belastning per kurs - C16:	50
Lekkasjestrøm [mA]:	0,7mA
Startstrøm Imax [A]:	16,5A
Startstrøm tid [µs]:	177µs
Produsent:	Philips
Tilkobling Primær:	18i5 DALI hann
Tilkobling Sekundær:	EPN0034 hunn



PRODUCT SHEET

Driver DALI 900mA Panel max 40W CLO 18i5 DALI/EPN0034

Art. no: 0300-2-04



Farge :

Hvit