



FDV SPEC SHEET

Arc Wall 850lm 830/840 12W 120° WH Opal Phasecut

Art. no: 6999-120-3-p



Arc Wall 850lm 830/840 12W 120° WH Opal Phasecut



Art. no: 6999-120-3-p

LYS TEKNISK

Lyskilde :	LED (innebygget)
Lumen ut (lm):	800
Spredningsvinkel [°]:	120
Fargetemperatur [K]:	3000-4000K
Forhåndsinnstilt Fargetemperatur	3000
Fargegjengivelse [CRI/Ra]:	80
Fargekode:	830/840
Fargetoleranse [SDCM]:	3
Optikk:	PC Opal

MONTERING / TILKOBLING

Tilkobling:	Terminal
Montering:	Vegg

PRODUKT

IP-grad:	IP20
Vandal klasse:	IK02
Driftstemperatur [°C]:	-20 - 40
Forventet Levetid :	L80: 100 000
Farge :	Hvit
Lengde [mm]:	314
Høyde [mm]:	88

ELEKTRISK DATA

Dimmetype:	Faseavsnitt
Systemeffekt [W]:	12-10-8
Forhåndsinnstilt Systemeffekt [W]:	12
Spenning [V]:	230V 50Hz
Isolasjonsklasse:	2
Nøddlys [t]:	Uten nøddlys